

SPECIFICATIONS



	MODEL PWC for personal watercraft	MODEL 750 for watercraft up to 750 lbs.	MODEL 1200 for watercraft up to 1,200 lbs.	MODEL 2000 for boats up to 2,000 lbs.	MODEL PONTOON for pontoon watercraft
MAX. WEIGHT CAPACITY	1,000 lbs.	750 lbs.	1,200 lbs.	2,000 lbs.	2,000 lbs.
WEIGHT	54 lbs.	92 lbs.	130 lbs.	162 lbs.	250 lbs.
OVERALL LENGTH	11'	17' 10"	17' 10"	17' 10"	17' 10"
OVERALL WIDTH	30"	Adjustable 21" - 24"	Adjustable 24" - 40"	Adjustable 33" - 49"	Adjustable*
RAIL WIDTH	Adjustable 11" - 14"	Adjustable 21" - 24"	Adjustable 24" - 40"	Adjustable 24" - 40"	Adjustable*
ROLLER TYPE	"Donut" shaped Polyolefin	"Donut" shaped Polyurethane	"Donut" shaped Polyurethane	Ribbed 4" wide Polyurethane	"Donut" shaped Polyurethane
NUMBER OF ROLLERS	14	12	16	24	52
NUMBER OF ROLLERS IN EXTENSION SECTION	12	10	12	16	28
ROLLER BEARING	Straight Bore	Delrin™ spanner and bushing	Delrin™ spanner and bushing	"Rocking" Delrin™ Sleeve	Delrin™ spanner and bushing
TILTING ROLLER AXLE	N/A	N/A	N/A	Yes	N/A
CONSTRUCTION	Aluminum	Aluminum	Aluminum	Aluminum	Aluminum
HARDWARE	Stainless Steel	Stainless Steel	Stainless Steel	Stainless Steel	Stainless Steel
WINCH	Zinc Plated	Zinc Plated	Zinc Plated	Zinc Plated	Zinc Plated
- "Dead lift" Rating	900 lbs.	1,100 lbs.	1,700 lbs.	1,700 lbs.	1,700 lbs.
- Gear Ratio	3:1	4:1	5:1	5:1	5:1
- Strap Length	15 feet	20 feet	25 feet	25 feet	25 feet
- Hook Type	Hook w/ Nylon PWC Loop	Standard Boat Hook	Standard Boat Hook	Standard Boat Hook	Standard Boat Hook
ANCHORING (included with kit)	N/A		Screw-in Ground Anchor with Hardware	Screw-in Ground Anchor with Hardware	Screw-in Ground Anchor with Hardware
MINIMUM REQUIRED ANCHORING	None Required unless using extension	Screw-in or Fasten to Wall or Footing	Screw-in or Fasten to Wall or Footing	Screw-in or Fasten to Wall or Footing	Screw-in or Fasten to Wall or Footing
WARRANTY	5 Years**	5 Years**	5 Years**	5 Years**	5 Years**

OPTIONS

EXTENSION SECTIONS	8 feet	8' 11"	8' 11"	8' 11"	8' 11"
WINCH UPGRADE AVAILABLE	N/A	N/A	1,500-lb. self-braking w/ 25' cable	1,500-lb. self-braking w/ 25' cable	1,500-lb. self-braking w/ 25' cable
CABLE UPGRADE	N/A	****	50'***	50'***	50'***
SUPPORT LEG KIT	N/A	Yes	Yes	Yes	Yes
WIDE SUPPORT KIT	N/A	Yes	Yes	Yes	Yes
FLOAT KIT	N/A	Yes	Yes	Yes	N/A

Roll-n-Go reserves the right to change design details, components and options at any time without notice.

* Adjustable rail width for round pontoons spaced between 66" and 82" on center.

** 2-Year warranty for salt water applications.

*** Available with upgraded winch only.

**** Customer may replace strap with up to 30 feet of 5/16" rope.

Using a Roll-n-Go is easy!



[Return to Roll N Go page](#)